






Unique TREAD DESIGN PERFECT TRACTION

*High Performance & Comfort Riding
for Medium to high intensity applications*

NEW STANDARD MODEL

-  **WIDER LUG AND MORE FOOT PRINT**
Increase Stability and grip , Increase stability and low heat buildup for improved efficiency.
-  **3-STAGE RUBBER COMPOUND**
Design for riding comfort and low heat buildup for improved efficiency lasting lifetime.
-  **Tread Compound Highly resistant to Cut and Chunk make the long lastign lifetime.**
Performance in medium to high duty applications.



Stability



Riding Comfort



Durabiity (Tire life)



Efficiency

SIZE	Rim	CLCK	TIRE DIMENSIONS		on fork lifts up to 25 km/h	
			OD (mm)	W (mm)	Load Wheel	SteeredWheel
5.00-8	3.00	●	447	117	1415	1090
15x4.5-8	3.00	●	377	115	1040	800
16x6-8	4.33	●	414	149	1495	1150
18x7-8	4.33	●	447.5	150	2145	1650
6.00-9	4.00	●	520	144	1885	1450
140/55-9	4.00	●	376	130	1170	900
21x8-9	4.00	●	518	179	2755	2120
6.50-10	5.00	●	574	162	2340	1800
200/50-10	6.50	●	456	195	2470	1900
23x9-10	6.50	●	578	192	3445	2650
7.00-12	5.00	●	644	173	2920	2240
28x9-15 (8.15-15)	6.50	●	695.5	211	3900	3000
28x9-15 (8.15-15)	7.00	●	696	212	3900	3000
8.25-15	6.50	-	797	205	4750	3650
250-15	7.00	-	722	228	4750	3650
250-15	7.50	-	722	228	4750	3650
300-15	8.00	-	806	251	5850	4500